

32 AMP
EC 350

EstrichBoy EC 350 BS

The powerful 32-amp
compressed air conveyor



For earth-moist screed

- Cement screed
- Calcium sulphate screed (anhydrite)
- Magnesia screed
- Vibration-laid tiling



A trick up your sleeve for working in green zones

The EstrichBoy EC 350 BS is quieter, with zero emissions and no diesel costs. With a 32-amp connection, it can be used on any construction site and the costs for its electricity supply can usually be charged at a flat rate through the construction site levy.

- Particularly suitable for noise-sensitive areas
- Optional innovative 16-amp additional unit for conveying at a width of up to 100 m and a height of up to 50 m*
- High delivery rates of 3 m³/h or 3.5 m³/h with the additional unit shorten working times and therefore reduce labour costs
- Reliable, robust and easy to use
- Weight of 1900 kg allows it to be towed by a range of towing machines



BRINKMANN



Optional unit for an additional performance boost



Standard 32 A socket and 16 A socket with optional additional unit



Storage box for essential tools



Robust keypad with a coloured LED display

Working lights

All the benefits at a glance

- Overload protection ensures interruption-free work
- Can be reduced to 25 amps if required for the construction site
- Intelligent delivery air control leads to shorter delivery times
- Premium service with original parts from certified workshops
- Shock-proof socket for lights, etc. is available

Equipment

	Series	Optional
Automatic brake adjustment	■	
Centralised lubrication system	■	
Height-adjustable car coupling	■	
Light carrier (12 V)	■	
Shock-proof connection	■	
Additional unit (5.5 kW)		■
Conversion to 100 km/h		■
High-pressure cleaner		■
Lifting eye		■
Light carrier (24 V)		■
Mixing time setting		■
Power cable 32A / 16A		■
Protective plate for feeder		■
Tool box (incl. guard bracket set)		■
Truck coupling		■
Special coating in RAL		■
Support feet		■
Wear plate on the dome		■
Wear plates, double-sided (on the front)		■
Wear plates, highly wear-resistant		■
Working lights		■

Technical data

	EstrichBoy EC 350 BS 32A	EstrichBoy EC 350 BS 32A with 16 A additional unit
Mixer drum	260 l, 200 l useful cap.	260 l, 200 l useful capacity
Output (theor)*	3 m ³ /h	3.5 m ³ /h
Delivery pressure*	8 bar	8 bar
Delivery range*	80 m wide, 40 m high	100 m wide, 50 m high
Air reservoir	400 l	400 l
Compressor	2.3 m ³ /min	2.7 m ³ /min
Drive motor	15 kW	20.5 kW
Weight	1900 kg	1900 kg
L x W x H	4800 x 1580 x 2450 mm	4800 x 1580 x 2450 mm
Filling height	400 mm	400 mm
Chassis	with automatic brake adjustment, up to 80 km/h permissible	
Special feature	hydraulic feeder and scraper	

*The data is based on empirical values and depends on the materials used

BRINKMANN
a brand of the Putzmeister Group
Max-Eyth-Straße 10 · 72631 Aichtal / Germany
Tel. +49 7127 599-0 · Fax +49 7127 599-743
brinkmann@estrichboy.de · www.estrichboy.de



BRINKMANN