



Electric

# EstrichBoy EC 260/45 Duo



## Semi-dry floor screed

- Cement screed
- Calcium sulphate screed (anhydrite)
- Magnesia screed
- Vibration-laid tiling (depending on consistency)



## Maximum electric power!

The EstrichBoy EC 260/45 Duo is powered solely by the site power supply while still delivering just as high an air output as the fuel-powered model.

The frequency-controlled electric motor, which enables switching between the 63 and 50 A operating modes, offers maximum flexibility and operational reliability.

The all-electric EstrichBoy EC 260/45 Duo comes in electrifying blue as standard. Operating an electric machine has never been this easy and reliable: Simply plug it in, load the material, mix it and start pumping.

- High output, improved efficiency
- Operating mode can be switched over at any time with maximum flexibility thanks to FlexDrive (63/50)
- Maximum operational reliability
- Zero emissions at a low sound level
- Low maintenance costs
- Optimum accessibility and ground clearance
- Lasting value and cost effectiveness thanks to high resale value



BRINKMANN



Simple connection with 63 A CEE outlet via provided 63 A cable



New, revised operating concept: The machine operator can view and adjust all necessary information straight from the operating position.



The new hood concept with removable rear section enables easy access to all important service and maintenance points

### Further advantages:

- **Technology “Made in Germany”**
- **Low wear and low maintenance requirements**
- **Flexible application options**
- **Configure “your” machine with a wide variety of equipment options**
- **First-class service thanks to extensive dealer service network**
- **Machine operator and technician training at our academy**

Technical data	EC 260/45 Duo	EC 260/45 Duo B	EC 260/45 Duo BS
Design	Basic version	With hydraulic feeder	With hydraulic feeder and scraper
Mixing vessel	260 l (200 l useful capacity)		
Delivery rate (theor.)*	3.8 m <sup>3</sup> /h	4.6 m <sup>3</sup> /h	5 m <sup>3</sup> /h
Delivery pressure	8 bar		
Compressor	4.35 m <sup>3</sup> /min		
Drive motor	Electric motor, 37 kW drive power, efficiency class IE3		
Weight	1,715 kg	1,840 kg	1,900 kg
Operating mode	63 / 50 A		
Length × width × height	5,067 × 1,525 × 1,840 mm	5,210 × 1,525 × 2,526 mm	5,210 × 1,525 × 2,526 mm
Filling height	820 mm	400 mm	400 mm
Maximum particle size	16 mm		
Chassis	Braked, approval up to 80 km/h, can be extended to 100 km/h as an option		
Mixer	Hydraulically driven, incl. reverse running and overload protection		

Equipment	EC 260/45 Duo
Manual lid	■
Radio remote control (BS model)	■
Series	
Central vessel outlet	■
Lifting eye	■
Car coupling	■
12 V light assembly	■
100 km/h axle	■
Connecting cable, 20 m, 63 A	■
Working light (12 V)	■
High pressure cleaner	■
High-wear plates (6 mm)	■
High-wear plates (Hardox, 8 mm)	■
Cable holder for 20 m cable	■
Customer labelling	■
Truck coupling	■
Optional	
24 V light assembly	■
Location system	■
Protective plate for feeder	■
Software package (mix counter + mixing time adjustment)	■
Special hood paintwork (blue as standard)	■
Support feet (vessel)	■
Polystyrene hopper	■
Wear plate on the dome	■
Wear plate, dished (both sides)	■
Water metering	on request
Toolbox	■

\* The data is based on experience and depends on the material properties. ■ Series ■ Optional